



Araldite® 2012

Application	Bonding for coffee tables
Substrates bonded	Marble, granite or wood is bonded to stainless steel or to chrome plated steel
Pretreatments	Degrease only
Design of joint	Various
Curing conditions	30 - 50 minutes at ambient temperature
Special service conditions	Bonded structure needs to have a good long-term durability
Advantages for the customer	Ease of application, rapid curing, pale colour
Advantages over competition	Competitors product has given application problems
Araldite® Adhesive used	Araldite® 2012
Customer location	Switzerland

Fast Facts

Two component epoxy paste adhesive

Fast curing

General purpose

Low shrinkage

Bonds a wide variety of materials

Tough and resilient

Ideal for bonding:

- GRP
- Stainless steel
- Aluminium
- Brass
- Ceramics

Statements in this release that are not historical are forward-looking statements. These statements are based on management's current beliefs and expectations. The forward-looking statements in this release are subject to uncertainty and changes in circumstances and involve risks and uncertainties that may affect the company's operations, markets, products, services, prices and other factors as discussed in the Huntsman companies' filings with the Securities and Exchange Commission. Significant risks and uncertainties may relate to, but are not limited to, financial, economic, competitive, environmental, political, legal, regulatory and technological factors. Accordingly, there can be no assurance that the company's expectations will be realised. The company assumes no obligation to provide revisions to any forward-looking statements should circumstances change, except as otherwise required by securities and other applicable laws. © 2007 Huntsman Advanced Materials Switzerland. © Araldite is a registered trademark of Huntsman Corporation or an affiliate thereof in one or more, but not all, countries.