



Araldite® 2047

Application	Bonding metal fasteners on the backside of mirrors
Substrates bonded	Steel to backside of mirror
Pretreatments	Degreasing with isopropanol
Design of joint	Overlapping joint
Curing conditions	Working time 5 minutes; curing: 5 minutes at room temperature to reach handling strength
Special service conditions	Exposure to moisture: the mirrors are also used in wet rooms (e.g. bathrooms)
Advantages for the customer	Very strong bonds; thus ability to bond metal fasteners on heavy mirrors; bond area takes high static loads on long term. Very good moisture resistance
Advantages over competition	Advantage over adhesive tapes: strong, durable joint over years
Araldite® Adhesive used	Araldite® 2047
Customer location	Germany

Fast Facts

Methacrylate adhesive requiring minimal surface pretreatment

Gap filling

Requires minimal surface treatment

Good properties on otherwise difficult to bond substrates

High impact resistance over a wide temperature range

Good performance particularly at low temperatures

Ideal for bonding:

- PMMA
- Polycarbonate
- Copper
- Brass
- Zinc and galvanised steel

Statements in this release that are not historical are forward-looking statements. These statements are based on management's current beliefs and expectations. The forward-looking statements in this release are subject to uncertainty and changes in circumstances and involve risks and uncertainties that may affect the company's operations, markets, products, services, prices and other factors as discussed in the Huntsman companies' filings with the Securities and Exchange Commission. Significant risks and uncertainties may relate to, but are not limited to, financial, economic, competitive, environmental, political, legal, regulatory and technological factors. Accordingly, there can be no assurance that the company's expectations will be realised. The company assumes no obligation to provide revisions to any forward-looking statements should circumstances change, except as otherwise required by securities and other applicable laws. © 2007 Huntsman Advanced Materials Switzerland. ® Araldite is a registered trademark of Huntsman Corporation or an affiliate thereof in one or more, but not all, countries.